according to 1907/2006/EC, Article 31



702100

Revision: 25.03.2021 Printing date: 25.03.2021

SECTION 01: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- · Trade name:

BEROPUR VA 15 - Conservation spray

· Article number:

80015484591

1.2 Relevant identified uses of the substance or mixture and uses advised against

This possess date about contains an expension of interrested form.

This safety data sheet contains an exposure scenario in an integrated form.

The product is intended for professional use.

· Application of the substance / the preparation

Protection wax

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Beropur AG Feldstr. 8 CH-8370 Sirnach

Telefon: 0041 - 71960 0727 Telefax: 0041 - 71960 0728 E-Mail: service@beropur.ch Internet: http://www.beropur.ch

· Further information obtainable from:

Product safety department.

• 1.4 Emergency telephone number:

Schweizerisches Toxikologisches Informationszentrum (STIZ): Tel. +41 44 251 66 66 24h-

Notfallnummer: +41 145 www.toxi.ch

SECTION 02: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02

Aerosol 1 - H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

STOT SE 3 - H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
- · Hazard pictograms





GHS02 GHS07

- Signal word Danger
- Hazard-determining components of labelling:

(Contd. on page 2)

according to 1907/2006/EC, Article 31



702100

Revision: 25.03.2021 Printing date: 25.03.2021

PRODUCT: BEROPUR VA 15 - Conservation spray

(Contd. of page 1)

Hydrocarbons C9-C10, n-alkanes, iso-alkanes, cyclics, <2% aromatics / Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains Sulfonic acids, petroleum, calcium salts. May produce an allergic reaction.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with local/regional/ national/international

regulations.

- · 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT:

Not applicable.

vPvB:

Not applicable.

SECTION 03: Composition/information on ingredients

- · 3.2 Chemical characterization: Mixtures
- Description:

Mixture of waxes

Propellant gas

· Dangerous components:

EC number: 203-448-7

substance with a Community workplace

exposure limit.

🏇 Flam. Gas 1A - H220; 🥏 Press. Gas

(Comp.) - H280

Hydrocarbons C9-C10, n-alkanes, iso-alkanes, 10,0 - <20,0

cyclics, <2% aromatics EC number: 927-241-2

Record number 01-2119471843-32 Asp. Tox. 1 - H304; Flam. Liq. 3 - H226; STOT SE 3 - H336; Aquatic

Chronic 3 - H412

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, 5 - <10,0

cyclics, <2% aromatics EC number: 919-857-5

(Contd. on page 3)

according to 1907/2006/EC, Article 31



702100

Revision: 25.03.2021 Printing date: 25.03.2021

	A	(Contd. of page 2)
	- H226; 🔱 STOT SE 3 - H336	
74-98-6	propane	5 - <10,0
	EC number: 200-827-9	
	substance with a Community workplace	
	exposure limit.	
	🅸 Flam. Gas 1A - H220; < Press. Gas	
	(Comp.) - H280	
61789-86-4	Sulfonic acids, petroleum, calcium salts	5 - <10,0
	EC number: 263-093-9	
	Record number 01-2119488992-18	
	♦ Skin Sens. 1B - H317	

SECTION 04: First aid measures

- 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Swallowing is not presumable (aerosol can).

- Information for doctor:
- 4.2 Most important symptoms and effects, both acute and delayed

Headache

Disziness

Vertigo

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 05: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

Foam, dry powder, carbon dioxide, water mist

• For safety reasons unsuitable extinguishing agents:

Water with full jet

• 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Fire gas of organic material has to be classed invariably as respiratory poison.

Vapours are heavier than air and spread on ground.

Product possibly swims up on surface and reinflames.

- 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

(Contd. on page 4)

according to 1907/2006/EC, Article 31



702100

Revision: 25.03.2021 Printing date: 25.03.2021

PRODUCT: BEROPUR VA 15 - Conservation spray

(Contd. of page 3)

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Heat increases pressure - aerosol cans may burst.

SECTION 06: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/ aerosol.

• 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

• 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 07: Handling and storage

· Handling:

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Keep away from sources of ignition - No smoking

Avoid contact with eyes and skin.

In case of formation of aerosols an adequate exhaustion is necessary.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

• 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

7.3 Specific end use(s)

No further relevant information available.

according to 1907/2006/EC, Article 31



702100

Revision: 25.03.2021 Printing date: 25.03.2021

PRODUCT: BEROPUR VA 15 - Conservation spray

(Contd. of page 4)

SECTION 08: Exposure controls/personal protection

8.1 Control parameters

• Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane

MAK (CH)

 Short-term value
 7600
 mg/m3

 3200
 ppm

 Long-term value
 1900
 mg/m3

 800
 ppm

74-98-6 propane

MAK (CH)

 Short-term value
 7200
 mg/m3

 4000
 ppm

 Long-term value
 1800
 mg/m3

 1000
 ppm

DNELs

Hydrocarbons C9-C10, n-alkanes, iso-alkanes,

cyclics, <2% aromatics

Dermal, DNEL: 77 mg/kg/d (worker) Dermal, DNEL: 46 mg/kg/d (consumer) Inhalative, DNEL: 871 mg/m³/d (worker) Inhalative, DNEL: 185 mg/m³/d (consumer)

Oral, DNEL: 46 mg/kg/d (consumer)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes,

cyclics, <2% aromatics

Dermal, DNEL: 208 mg/kg/d (worker) Inhalative, DNEL: 871 mg/m³/d (worker)

Additional information:

The lists valid during the making were used as basis.

- 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Do not eat, drink, smoke or sniff while working.

Apply solvent resistant skin cream before starting work.

Use skin protection cream for skin protection.

Be sure to clean skin thoroughly after work and before breaks.

Do not carry product impregnated cleaning cloths in trouser pockets.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Combined filter: Particle-filtering half mask (filter P2 or P3) and gas filter type AX

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Solvent resistant gloves

Material of gloves

(Contd. on page 6)

according to 1907/2006/EC, Article 31



702100

Revision: 25.03.2021 Printing date: 25.03.2021

PRODUCT: BEROPUR VA 15 - Conservation spray

(Contd. of page 5)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material: >= 0,7 mm

Permeation time >= 480 minutes

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:

Safety glasses

· Body protection:

Flame retardant and antistatic protective clothing

9.1 Information on basic physical and che	emical properties
General Information	
Appearance:	
Form:	Aerosol
Colour:	Light beige
Odour:	Mild
Odour threshold:	Not determined.
pH-value:	Not applicable.
Change in condition	
Initial boiling point and boiling range:	< -30,0 °C
Flash point:	< -60,0 °C Theoretical value Not applicable, as aerosol.
Flammability (solid, gas):	Not applicable.
Auto-ignition temperature:	Not determined.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	1,40 Vol %
Upper:	10,80 Vol %
Vapour pressure:	Not determined.
Density:	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	29,67 %
VOC (EC)	560,00 g/l 74,6891 %
Solids content:	26,00 %
9.2 Other information	No further relevant information available.

CH ·

according to 1907/2006/EC, Article 31



702100

Revision: 25.03.2021 Printing date: 25.03.2021

PRODUCT: BEROPUR VA 15 - Conservation spray

(Contd. of page 6)

SECTION 10: Stability and reactivity

10.1 Reactivity

No further relevant information available.

- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

• 10.3 Possibility of hazardous reactions

Danger of bursting.

Forms explosive gas mixture with air.

10.4 Conditions to avoid

Flames, sparks, heat.

• 10.5 Incompatible materials:

Strong oxidizing agents

· Dangerous reactions

Forms explosive gas mixture with air.

• 10.6 Hazardous decomposition products:

Danger of forming toxic pyrolysis products.

Additional information:

No further relevant information available.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity
- LD/LC50 values relevant for classification:

106-97-8 butane

Inhalative, LC50/4h: 658 mg/l (rat)

Hydrocarbons C9-C10, n-alkanes, iso-alkanes,

cyclics, <2% aromatics

Oral, LD50: > 5000 mg/kg (rat)

Dermal, LD50: > 5000 mg/kg (Rabbit)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes,

cyclics, <2% aromatics

Oral, LD50: > 5000 mg/kg (rat)

Dermal, LD50: > 5000 mg/kg (Rabbit)

Inhalative, LC50: > 5000 mg/l (rat) (8h, vapour)

61789-86-4 Sulfonic acids, petroleum, calcium salts

Oral, LD50: >16000 mg/kg (rat) Dermal, LD50: >=4001 mg/kg (rat)

- Primary irritant effect:
- Skin corrosion/irritation

Frequent resp. persistent skin contact may degrease skin, what may cause skin complaints and dermatitis.

· Serious eye damage/irritation

No irritating effect.

Respiratory or skin sensitisation

May produce allergic reactions

Specific Concentration Limit for CAS-No. 61789-86-4: >= 10 %

Additional toxicological information:

The risk assessment of the preparation concerning adverse health effects is based on the available data.

After inhalation of vapors: irritations of mucous membranes, drowsiness; in high doses: head aches, nausea, vomiting, dizziness, narcosis

Contact with eyes may cause irritation.

(Contd. on page 8)

according to 1907/2006/EC, Article 31



702100

Revision: 25.03.2021 Printing date: 25.03.2021

PRODUCT: BEROPUR VA 15 - Conservation spray

(Contd. of page 7)

Inhalation of spray mist / aerosols may cause irritation of the mucous membranes of respiratory tract. Frequent resp. persisting skin contact may lead to skin complaints and dermatitis.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

The substance is not known as mutagenic. The substance is not known as cancerogenic. The substance is not known as toxic to reproduction.

STOT-single exposure

The classification criteria are met

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- 12.1 Toxicity
- · Aquatic toxicity:

61789-86-4 Sulfonic acids, petroleum, calcium salts

LC50: >=10000 mg/l (Activated sludge)

· 12.2 Persistence and degradability

No further relevant information available.

- · Behaviour in environmental systems:
- 12.3 Bioaccumulative potential

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

- Additional ecological information:
- General notes:

Do not allow product to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- PBT:

Not applicable.

vPvB:

Not applicable.

12.6 Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

After prior treatment product has to be landfilled or incinerated adhering to the regulations pertaining to the disposal of especially hazardous waste.

· Waste disposal key:

The waste key number has to be specified acc. European Waste Catalogue (depending on branches and processes).

- Uncleaned packaging:
- · Recommendation:

Also empty containers are still contaminated and have to be disposed by specialists or must be subjected to recondition. Waste key number: 150110 (EAK)

СН

according to 1907/2006/EC, Article 31



702100

Revision: 25.03.2021 Printing date: 25.03.2021

PRODUCT: BEROPUR VA 15 - Conservation spray

(Contd. of page 8)

SECTION 14: Transport information

• 14.1 UN-Number

ADR UN1950
IMDG UN1950
IATA UN1950
• 14.2 UN proper shipping name

ADR 1950 AEROSOLS IMDG AEROSOLS

IATA AEROSOLS, FLAMMABLE

• 14.3 Transport hazard class(es)

ADR

 Class
 2 (5F) Gases

 Label
 2.1



IMDG

Class 2.1

Label



IATA

Class 2.1

Label



• 14.4 Packing group

ADR -IMDG -IATA -

• 14.5 Environmental hazards:

Not applicable.

14.6 Special precautions for user

Warning: Gases.

Danger code (Kemler): 23
EMS Number: F-D,S-U

 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

• Transport/Additional information:

Not applicable.

Excepted quantities (EQ): E0
Limited quantities (LQ) 1L
Transport category 2

(Contd. on page 10)

according to 1907/2006/EC, Article 31



702100

Revision: 25.03.2021 Printing date: 25.03.2021

PRODUCT: BEROPUR VA 15 - Conservation spray

D

(Contd. of page 9)

Tunnel restriction code

_

IMDG

Limited quantities (LQ) 1L
Excepted quantities (EQ) E0

• UN "Model Regulation":

UN 1950 AEROSOLS, 2 (2.1)

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

• REGULATION (EC) No 1907/2006 ANNEX XVII

Conditions of restriction: 3, 40

· National regulations:

For components with workplace-related limit values →that require monitoring, see Section 8.1

· Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out for the mixture.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The information is believed to be correct, but comprehensive and is to be used for guidance only, which is based on current knowledge of the chemical or mixture and applicable to appropriate safety precautions for the product.

• Relevant phrases

H220	Extremely flammable gas.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

VCI: Verband der chemischen Industrie, Deutschland (German chemical industry association)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 11)

Page: 11 / 11

Safety data sheet

according to 1907/2006/EC, Article 31



702100

Revision: 25.03.2021 Printing date: 25.03.2021

PRODUCT: BEROPUR VA 15 - Conservation spray

(Contd. of page 10)

vPvB: very Persistent and very Bioaccumulative

• * Data compared to the previous version altered.